Inter-Tech Elektronik Handels GmbH

IPC 1U-K-125L

The **IPC 1U-K-125L** is the perfect rack for a small and cost-effective server system. Its compact design and its small installation depth of 250mm for ITX boards allows this case to fit in to nearly every rack.

The **IPC 1U-K-125L** provides internal space for optional 1x 3.5" or 2x 2.5" hard drives. Three standard 40mm fans, which are internally mounted behind the front panel, ensure a reliable and optimal cooling.

In the front are two USB 2.0 ports next to the controls.

Specifications

Motherboard	ITX
Drive Bays	5.25" external: 0
	3.5" internal: 1/0*
	2.5" internal: 0/2*
Front Connectors	USB 2.0: 2
Cooling System	Internal: 3x 40mm
	(included, Molex connector)
Controls	Power-Button
	Reset-Button
LED	Power
	HDD Activity
	Network Activity
	Overheating Alert
	Power Failure
Material	1.0/1.2mm Steel
Packing Units	Shipping Unit: 1 Piece
	Pallet: 65 Pieces
Guarantee and Warranty	Case 24 Months Warranty
Article Number	88887085
EAN-Code	4260133125711
Scope of Delivery	Screw Set
	I/O shield for standard ITX mainboards
Features	Only 250mm Depth
	3x 40mm fans included
	USB 2.0 intern as block connector
Accessories	I/O Shield K-125-1 for Intel® D2700MUD (D2500HN)
	(Art. 88887066)
	I/O Shield K-125-2 for Intel® D2500CC (D525MW)
	(Art. 88887067)
	Universal I/O shield
	(Art. 88887181)

*When using a 3.5" hard drive, it is not possible to install any 2.5" hard drive

Dimensions and Weight

	Cage	Case	Package
Height	45mm	45mm	115mm
Width	430mm	485mm	560mm
Depth	250mm	285mm	415mm

Weight (net): 2.79Kg
Weight (gross): 3.91Kg

Power Supply

Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	
P8 12V 8Pin	-	
PCI-Express 6+2Pin	-	
PCI-Express 6Pin		-
IDE 4Pin		-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	-	-

Without

Certification: RoHS CE

Errors excepted. No warranty for the correctness of the information State: 28.04.2015